

<b>PARAMETER</b>	<b>ISNR 3L</b>	<b>ISNR 5</b>	<b>ISNR 10</b>	<b>ISNR 20</b>	<b>ISNR CV 50</b>	<b>ISNR CV 60</b>	<b>TEST METHOD</b>
1.DIRT5WT	0.03 MAX	0.05 MAX	0.03 MAX	0.03 MAX	0.03 MAX	0.03 MAX	TCVN 6089 : 2004
2.VOLATILE MATTER % WT	0.80 MAX	0.80 MAX	0.03 MAX	0.03 MAX	0.03 MAX	0.03 MAX	TCVN 6088 : 2004
3.ASH % WT	0.50 MAX	0.60 MAX	0.03 MAX	0.03 MAX	0.03 MAX	0.03 MAX	TCVN 6087 :2004
4. NITROGEN % WT	0.60 MAX	0.60 MAX	0.60 MAX	0.60 MAX	0.60 MAX	0.60 MAX	TCVN 6091 : 2004
5. PO	35 MIN	30 MIN	30 MIN	30 MIN	-	0.60 MAX	TCVN 60892 : 2004
6. PRI	60 MIN	60 MIN	50 MIN	40 MIN	60 MIN	60 MIN	TCVN 6092 : 2004
7. COLOUR	6 MAX	-	-	-	-	-	TCVN 6093 : 2004
8.MOONEY VISCOSITY ML	-	-	-	-	60 (+_5)	50(+_5)	TCVN 6090 : 2004
9. RHEOMETRIC CURE (160 OC,10 ARC 100RPM.ACS 1)	R	-	-	-	R	R	TCVN 6090 :2004